

IDC SFXPro4104 Satellite Receiver

Audio pinout 4x DB-9 (Male on chassis): Build adapter cable w/Female DB-9

NOTE: DB9 Analog audio pinout/gender is the same as SRPro Stream Decoders

The SFX Pro Audio receiver audio 9-pin male pin out:
• Pin-1, Analog Left Out -
• Pin-2, Analog Left Out +
• Pin-3, AES +
• Pin-4, Analog Right Out -
• Pin-5, Analog Right Out +
• Pin-6, Analog Left Ground
• Pin-7, AES Ground
• Pin-8, AES -
• Pin-9, Analog Right Ground

Relay pinout 4x DB-15 (Male on chassis): Build cable w/Female DB-15

The SFX Pro Audio receiver relay 15-pin male pin out:
• Pin-1, Unused
• Pin-2, Relay-1 A pin (NO)
• Pin-3, Relay-2 A pin (NO)
• Pin-4, Relay-3 A pin (NO)
• Pin-5, Relay-4 A pin (NO)
• Pin-6, Unused
• Pin-7, Relay-1 C pin (NC)
• Pin-8, Relay-2 C pin (NC)
• Pin-9, Unused
• Pin-10, Relay-1 B pin (Common)
• Pin-11, Relay-2 B pin (Common)
• Pin-12, Relay-3 B pin (Common)
• Pin-13, Relay-4 B pin (Common)
• Pin-14, Relay-3 C pin (NC)
• Pin-15, Relay-4 C pin (NC)

dab rev5 5/6/2011